

CCTV IP / Professional NVRs

SF-NVR6108-4KE-8P

Network Video Recorder for IP Cameras

4K NVR 6 VS2 Series

Network recorders with great flexibility of use, even with ultra-high resolution 4K cameras or highly efficient H.265+ encoding. Monitoring up to 1 Ch@4K or 4 Ch@1080p with auto-adaptive mode that achieves simultaneous display of a large number of cameras without exhausting graphic resources. Its 4K HDMI output allows maximum use of UHD monitors. Versions with integrated PoE power supply and auto-add-on mode for simplified and centralised installation.

- 8Channels IP video
- Decoding capacity 8MP
- Compression technology H.265+/H.265
- Total bandwidth 80 Mbps
- PoE (Power Over Ethernet) technology
- 4K HDMI and VGA Output
- Space for 1 HDD



Technical Specification

| | |
|----------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------|
| Entrada de vídeo IP | 8-ch |
| HDMI Output | 1-ch, 4K (3840 × 2160)/30Hz, 1920 × 1080p/60Hz, 1600 × 1200/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz; HDMI/VGA simultaneous output |
| VGA Output | 1-ch, 1920 × 1080p/60Hz, 1600 × 1200/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz ;HDMI/VGA simultaneous output |
| Incoming Bandwidth | 80 Mbps |
| Outgoing Bandwidth | 80 Mbps |
| Salida de audio | 1-ch, RCA (Linear, 1 K Ω) |
| Two-Way Audio | 1-ch, RCA (2.0 Vp-p, 1 k Ω) |
| Formato de decodificación | H.265+,H.265,H.264+,H.264 |
| Decodificación | 4-ch@1080p |
| Reproducción síncrona | 8-ch |
| Resolución de grabación | 8 MP/6 MP/5 MP/4 MP/3 MP/1080p/UXGA /720p/VGA/4CIF/DCIF/ 2CIF/CIF/QCIF |
| Protocolo de red | TCP/IP, DHCP, Safire Connect, DNS, DDNS, NTP, SADP, SMTP, NFS, iSCSI, UPnP™, HTTPS |
| Interfaz de red | 1, RJ-45 10/100 Mbps self-adaptive Ethernet interface |
| Interfaz | 8-ch |
| alimentación | ≤ 75W |
| RAID Type | No |
| SATA | 1 SATA interface |
| Capacidad | Up to 8TB capacity for each disk |
| Interfaz USB | 2 × USB 2.0 |
| Fuente de alimentación | 48 VDC, 1.8 A |
| Consumo | ≤ 10 W (without enabling PoE) |
| Temperatura de trabajo | -10 to +55° C (+14 to +131° F) |
| Condiciones de Humedad | 10 to 90 % |
| Chassis | 1U chassis |
| Dimensión (W × D × H) | 320 × 240 × 48 mm (12.4" × 9.4" × 1.9") ≤ 1 kg (2.2 lb) |