

SF-SW1816HIPOE-GF-300

Safire Switch Hi-PoE

16 PoE ports + 2 SFP

Gigabit port speed 10/100/1000Mbps

14 PoE+ Ports 30W + 2 Hi-PoE Ports

60W

PoE Watchdog

Up to 300W Total PoE Power



Desktop Switch

14 PoE+ ports 30W RJ45 10/100/1000 Mbps

2 Hi-PoE+ ports 60W 802.3bt 10/100/1000Mbps + 2 Uplink SFP 10/100/1000Mbps

Supports PoE power supply up to 300W in total for all ports

AI Watchdog

Specifications

| | |
|------------------------------|--|
| Interface | 16 PoE + 2 Uplink SFP ports |
| Port speed RJ45 | 16x 10/100/1000Mbps + 2x 10/100/1000Mbps |
| PoE features | Up to 300W in total for all ports Ports 1-14 PoE+ Up to 30W 802.3af/at Port 15-16 Hi-PoE Up to 60W 802.3af/at/bt |
| Transmission distance | 130 meters |
| Bandwidth | 36Gbps |
| MAC Table | 8K |
| Latency | 10 to 100MBps < 16?s (using 64 packet size byte) |
| AI PoE | PoE Watchdog Ports 1-16 - Automatic restart of the power supply to a PoE port when a possible failure is detected. |
| Power | Front Take 90-240V |
| Protections | 6KV against Rays 8KV ESD Protection |
| Operating temperature | -30° C ~ 60° C |
| Dimensions | 18 (D) x 45 (H) x 430 (W) mm |
| Weight | 2,65Kg |