

Networking / Switches / Unmanaged

SF-SW2016HIPOE-GF-300

SAFIRE



Features

- Desktop Switch
- 14 PoE+ ports 30W RJ45 10/100/1000 Mbps
- 2 Hi-portsPoE+ ports 60W 802.3bt 10/100/1000Mbps + 2 Uplink SFP 10/100/1000Mbps + 2 Uplink RJ45 10/100/1000Mbps
- Supports PoE power supply up up 285W in total for all ports
- AI Watchdog

Specifications

Interface	16 PoE ports + 2 Uplink RJ45 + 2 SFP Uplink
Port speed RJ45	18x 10/100/1000Mbps + 2x 10/100/1000Mbps
PoE features	Up to 285W in total for all ports Port 1 and 2 Hi-PoE Up to 60W 802.3af/at/bt Ports 3~16 PoE+ Up to 30W 802.3af/at
Bandwidth	40Gbps
MAC Table	2K
AI PoE	PoE Watchdog Ports 1~16 - Automatic restart of the power supply to a PoE port when a possible failure is detected.
Functions (Dip switch)	VLAN: Isolation mode, 1-16 ports isolated from each other, communication with 17-18 ports, port PoE watch mode enabled. Default: Normal mode, all interfaces can communicate with each other, transmission distance: 100 meters, transmission rate: 10 M/100 M/1 Adaptive G, port PoE monitoring mode off. Extension: Link extension mode, PoE power supply of 9-16 ports and data transmission, extendable distance up to 250 meters, transmission rate: 10 Mbps, port PoE watch mode enabled.
Power	AC 100-240V 50/60Hz DC 52V 5.76A
Protections	6KV against Rays 8KV ESD Protection
Operating temperature	0 - 40° C
Dimensions	207 (D) x 45 (H) x 320 (W) mm